

HPRT Bravo/ Bingo

Industrial Barcode Specification



| Model | HPRT Bravo | HPRT Bingo |
|---------------------------------|---|---|
| Printing Method | Direct Thermal/Transfer Thermal | |
| Resolution | 203 dpi/8 ips | 203 dpi/14 ips |
| Max.Printing Speed | Optional 300 dpi/6 ips | Optional 300 dpi/8 ips or 600 dpi/4 ips |
| Max.Printing Length | 2286mm(203 dpi) 1524mm(300 dpi) | 1524mm(300 dpi); 762mm(603 dpi) |
| Max.Printing Width | 104mm | |
| PictBridge | ZPL, DPL, EPL | |
| Printing Media Type | Continuous paper, seam label paper, Black Label paper, punched paper, environmental protection thermal label paper, special coated paper, synthetic fiber label paper, textile belt | |
| Printing Media Diameter | 1.5 inches/3 inches inner diameter Maximum 10-inch outer diameter | |
| Printing Media Thickness | 80µm~250µm | |
| Printing Media Width | 25mm~120mm | |
| Ribbon Type | Wax, Resin, Wax and resin mixture | |
| Ribbon Die | 1 inch | 1 inches |
| Ribbon Width | 30mm~110mm | |
| Ribbon Length | 450 meters | 600 meters |

| | | |
|------------------------------------|--|-------------------------------------|
| Sensor Configuration | Print mechanism off detection, Ribbon off detection, Media off detection, thermal over-temperature detection, Seam label/punched label/Black label positioning detection, motor over-temperature detection | |
| Standard Communication Port | 1 USB-B, 3USB HOST | |
| | 1 Ethernet Port, 1 RS232 Serial Port | |
| Optional Communication Port | Parallel Port or Labeller Poer, Wi-Fi | |
| | RFID(UHF) | |
| RAM | 512 MB | |
| Flash | 256 MB | |
| Operation window | 4 status lights, 8 buttons | 4 status lights, 6 buttons |
| | 3.5-inch colour display | 3.5-inch colour touch screen |
| Optional accessories | Label peeling module, label liner rewinding device, Cutting Module | |
| Dimension(L*W*H) | 460.4x263.6x330.5 mm | |
| Weight | 12.5 kg | |
| Security Specification | CE, FCC, CCC, CB, UL, RoHS, WEEE | |
