



RP76IV Thermal Transfer Direct Thermal Printer

Printing	Resolution	203dpi (High Resolution and High Speed)
	Printing method	Thermal Transfer/Direct Thermal
	Printing speed	4-5 Inch/s
	Max printing width	104mm (4.09")
	Max printing Length	2286mm (90")
	Interface	USB/ (USB+ Serial+Parallel+Ethernet)
	Print head (abrasivaresistance)	50km
Ribbon	Commands	TSC
	Ribbon OD	Max 60mm
	Ribbon Length	Max 300M
	Ribbon width	Min. 30mm; Max. 110mm
	Ribbon Core Size	25.4mm
Media	Ribbon Rolling Up Method	Outward Rolling
	Max Media Roll OD	127mm (5")
	Min Media Roll ID	25mm
	Media Paper Type	Continuous, gap, fan fold, black mark,
	Media Rolling Up Method	Printing side outward Rolling
	Media width	Max 120mm (4.72"), Min: 20mm (0.78")
	Media Roll Core Size	25.4mm~38mm
	Media Gap	Min.2mm
	Media Thickness	0.058mm~0.305mm
	Label Length	10mm~2286mm
Software	Accessories	External Media Holder (Optional)
	Editing Software	Nicelabel SE
Character font	Driver	Windows 2000 XP, Vista, Win7, Win8, Windows Server 2003&2008
	Character Set	GB18030
Barcode type	Print font	ASCII Font A: 12*24 ASCII Font B: 9*24
	1D code	Code39, Code93, Code128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-13, EAN-14, EAN-128, UPCA, UPCE, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, ITF14
Picture format	2D code	QR code
	Graphics processing	Support BMP/PCX/BAS
Environment Specification	Temperature	Working: 5-45°C, Storage: -10~50°C
	Humidity	Working: 25%~85%; Storage: 10%~90%
Power supply		Input: AC 110V/240V, Output: DC24V/2.5A,60W
Storage		4MB
Dimension		223*286*169mm
Printer weight		2.35kg