

RP-80US/UP/USE

POS Printer - Reliable Printing Solution

Technical Specifications

Physical characteristics

Dimensions : 195×145×148mm

Weight : 2.3kg

Print

Printing Method : Thermal line

Effective Printing Width : 72mm

Resolution : 203dpi (8dot/mm)

Printing Speed : Max:250mm/S

Paper Specification

Paper Width : 79.5 ±0.5mm

Paper Roll Diameter : 80mm

Paper Supply Method : Easy paper loading

Barcodes type

Barcodes type : UPC-A, UPC-E, EAN-13, EAN-8, EAN-39, CODE39, ITF, CODEBAR, CODE93, CODE128, PDF417, QRCODE

Extended character table: PC437, Katakana, PC850, PC860, PC863, PC865, WPC1252, PC866, PC852, PC858

Reliability

MCBF : 60 million lines

TPH : 100 million pulses (100KM)

Auto cutter : 1,000,000 cuts

Interface

RP80 US : USB + Serial

RP80 UP : USB+ Parallel

RP80 USE : USB+ Serial + Ethernet

Printing Command

Compatible ESC/POS/OPOS

NV bitmap Flash size

64KBytes

Drivers

Windows 2000/XP/7/vista/8/Linux

Power Adapter

DC 24V, 2.5A

Port Control

DC 24V, 1A

Certificate

FCC, CB

Environment

Temperature

Operating : 0 ~ 45°C

Stock : -10 ~ 50°C

Humidity

Operating : 10 - 80%

Stock : -10 ~ 90% (exclude paper roll)



Auto-Cutter



Drop-in Paper Load



Wall Mountable



Ethernet

Application:



Retail



Cafes



Grocery



Ticketing



Kiosk